

WeldTec®

Rocker™ TIG Torches

The new Rocker™ torches take the stress out of pipe and tube welding.

- No more cable binding or twisting
- Precise torch control
- Less hand and wrist fatigue
- Ideal for walking the cup
- Flex neck and gas valve models

Weldtec's patented rocker cable connection allows the torch body to rock back and forth on the power cable without binding or twisting. This greatly reduces strain and tension on the welders hand allowing longer weld cycles with reduced down time. Ideal for pipe and tube welding.

The Rocker™ rubber power cable provides more welding amps than the standard 9 and 17 model torches.



Made in America.

ORDERING INFORMATION

TORCH SERIES*	MODEL	AMPS*	TORCH PACKAGE	LENGTH	FLEX	VALVE
9FV	R-9FV	150	R-9FV-12R	12.5 Ft.	✓	✓
			R-9FV-25R	25 Ft.	✓	✓
9V	R-9V	150	R-9V-12R	12.5 Ft.		✓
			R-9V-25R	25 Ft.		✓
17FV	R-17FV	180	R-17FV-12R	12.5 Ft.	✓	✓
			R-17FV-25R	25 Ft.	✓	✓
17V	R-17V	180	R-17V-12R	12.5 Ft.		✓
			R-17V-25R	25 Ft.		✓

*Uses industry standard parts compatible with 9 and 17 style torches.

*AC, DCSP

Add a quick connector to make a TIGrig™ set-up for field welding. Works with air cooled torches and standard rubber power cables. Standard 5/8 RH inert gas hose connection and Tweco® style plug.

OPTIONAL - TIGrig™ SET-UP

DESCRIPTION	PART NO.	TORCHES	CABLES
Quick Connector, plug only	TTC-150	9, 17 Series Air Cooled	1 Pc. Rubber
Quick Connector, plug & gas hose 5/8 RH-FM	TTC-150G		
Quick Connector, plug & gas hose 1/4 NPT-M	TTC-150P		

Specifications subject to change without notice.



R-17FV torch with "XL" gas lens.

Special Rocker™ rubber power cable.

TIGrig™ TTC-150G Connector (Optional)



Torch body is free to rock back and forth without binding or twisting of cable.